

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	
Model #	FI10220VLFBRT-	FI10222VLFBRT-	FI10224VLFBRT-	FI10226VLFBRT-	FI10228VLFBRT-	FI10230VLFBRT-	
Model #	100	100	100	100	100	100	
CAPACITIES							
GVWR (lbs)			99	000			
GAWR (lbs/axle)			50	000			
CHASSIS							
Frame		6" x 2" S	teel Tube		8" x 2" S	teel Tube	
Tongue		12" Extension, 6" x	2" Steel Triple Tube		12" Extension, 8" x	2" Steel Triple Tube	
Crossmembers			•	16" On-Center		•	
Coupler			2-5/16" <i>A</i>	Adjustable			
Safety Chains			DOT Co	mpliant			
Tongue Jack		2K Se	t-Back		5K Se	t-Back	
Wall Studs			Steel Tube, 1	6" On-Center			
Roof Bows			Steel Tube, 1	6" On-Center			
Front Profile			F	at			
Beavertail			4	8"			
Ramp(s)		16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
Side Door		48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
Vents	(1) Manual Roof, Sidewall Airflow						
Fenders				Aluminum			
Axle		(2) 52	200 lb. Torsion Brake		ıration		
Hubs				Lube			
Breakaway			•	h, and Lanyard			
Tires				R15D 8-PR			
Wheels				e Aluminum			
Exterior Finish				luminum			
Undercoating				notive			
Exterior Fastening	5 5" D. H 5.4			l (Screwless)	D. (0	. 01-1-1 011	
Exterior Trim	5.5" Bottom Ext		• •	•	uminum Roof Corners	s, Stainiess Steel	
Stone Guard			Radius Corners, Stair	ATP	μ		
Rear Spoiler				el Flare with Taper			
Roof				less Aluminum			
Roof Cap			•	ss Steel			
Interior Walls				, Engineered Wood			
Interior Trim			-	m Wall Transitions			
Ceiling		Insulation. Vinvl	Ceiling Transitions, V		Aluminum Coves		
Flooring			•	eered Wood			
Interior Lights				I" LED			





	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30			
Model #	FI10220VLFBRT-	FI10222VLFBRT-	FI10224VLFBRT-	FI10226VLFBRT-	FI10228VLFBRT-	FI10230VLFBRT-			
Model #	140	140	140	140	140	140			
CAPACITIES									
GVWR (lbs)			140	000					
GAWR (lbs/axle)			70	00					
CHASSIS									
Frame			8" x 2" S	teel Tube					
Tongue			12" Extension, 8" x	2" Steel Triple Tube					
Crossmembers			Formed Steel,	16" On-Center					
Coupler			2-5/16" A	djustable					
Safety Chains			DOT Co	mpliant					
Tongue Jack			7K Drop Le	g, Set-Back					
Wall Studs			Steel Tube, 1	6" On-Center					
Roof Bows			Steel Tube, 1	6" On-Center					
Front Profile				at					
Beavertail		48"							
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist								
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback								
Vents	(1) Manual Roof, Sidewall Airflow								
Fenders				Aluminum					
Axle		(2) 70	000 lb. Torsion Brake,	•	ration				
Hubs			•	Lube					
Breakaway			•	h, and Lanyard					
Tires				R16E 10-PR					
Wheels			•	Aluminum					
Exterior Finish				uminum 					
Undercoating			Auton						
Exterior Fastening	E E'' Dettem Ext		VHB Bonded	,	.m.inm. Daaf Carnara	Ctainless Ctasl			
Exterior Trim	5.5 Bottom Exti		uck Body Top Extrusi Radius Corners, Stair			s, Stainless Steel			
Stone Guard			24"	·	,				
Rear Spoiler				I Flare with Taper					
Roof				less Aluminum					
Roof Cap			•	ss Steel					
Interior Walls				, Engineered Wood					
Interior Trim				m Wall Transitions					
Ceiling		Insulation, Vinvl	Ceiling Transitions, V		Aluminum Coves				
Flooring		, , , , , , , ,	•	eered Wood					
Interior Lights				l" LED					







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V						
Cargo Control	(4) 5000 lb. Recessed D-Rings						
Connector Plug	Round 7-pin Blade						
Exterior Lights	(2) Rear LE	D Loading, (4) Additi	onal Stop/Turn/Tail, F	ull LED, DOT Compl	iant, Integrated Backu	p/Taillights	
HVAC	Bracing and Wire for HVAC						





	8.5 x 32	8.5 x 34			
Model #	FI10232VLFBRT-140	FI10234VLFBRT-140			
CAPACITIES					
GVWR (lbs)	14	000			
GAWR (lbs/axle)		000			
CHASSIS	•				
	011 011 6	N 17-1			
Frame		Steel Tube			
Tongue		2" Steel Triple Tube			
Crossmembers		, 16" On-Center			
Coupler		Adjustable			
Safety Chains		ompliant			
Tongue Jack	·	eg, Set-Back			
Wall Studs	·	16" On-Center			
Roof Bows	·	16" On-Center			
Front Profile		lat			
Beavertail		18"			
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist				
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback				
Vents	(1) Manual Roof, Sidewall Airflow				
Fenders		Aluminum			
Axle	• • • • • • • • • • • • • • • • • • • •	, Spread Axle Configuration			
Hubs	•	/ Lube			
Breakaway	**	ch, and Lanyard			
Tires		R16E 10-PR			
Wheels		e Aluminum			
Exterior Finish		luminum			
Undercoating		motive			
Exterior Fastening		d (Screwless)			
Exterior Trim		ion, Polished Cast Aluminum Roof Corners, Stainless Steel			
0. 0 1		nless Steel Rear Hoop			
Stone Guard		ATP			
Rear Spoiler		el Flare with Taper			
Roof Con	•	nless Aluminum			
Roof Cap		ess Steel			
Interior Walls		y, Engineered Wood			
Interior Trim		ım Wall Transitions			
Ceiling		White Vinyl Liner with Aluminum Coves			
Flooring	•	eered Wood			
Interior Lights	· , ,	1" LED			
Switches	* * * * * * * * * * * * * * * * * * * *	V, (1) Top Fuel Load Light, 12V			
Cargo Control	(4) 5000 lb. Re	ecessed D-Rings			







	8.5 x 32	8.5 x 34			
Connector Plug	Round 7-	pin Blade			
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights				
HVAC	Bracing and V	Vire for HVAC			





	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Model #	FI10224VLFBRT-	FI10226VLFBRT-	FI10228VLFBRT-	FI10230VLFBRT-	FI10232VLFBRT-	FI10234VLFBRT-			
Model #	160	160	160	160	160	160			
CAPACITIES									
GVWR (lbs)			160	000					
GAWR (lbs/axle)			80	00					
CHASSIS									
Frame			8" x 2" S	teel Tube					
Tongue			12" Extension, 8" x	2" Steel Triple Tube					
Crossmembers			Formed Steel,	16" On-Center					
Coupler			2-5/16" A	djustable					
Safety Chains			DOT Co	mpliant					
Tongue Jack			12K Drop Le	eg, Set-Back					
Wall Studs			Steel Tube, 1	6" On-Center					
Roof Bows			Steel Tube, 1	6" On-Center					
Front Profile				at					
Beavertail		48"							
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist								
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback								
Vents	(1) Manual Roof, Sidewall Airflow								
Fenders		4.4		Aluminum					
Axle		(3) 80	000 lb. Torsion Brake,	•	ration				
Hubs				Bath					
Breakaway 			•	h, and Lanyard					
Tires				7.5J 18-PR					
Wheels			•	e Aluminum					
Exterior Finish				uminum					
Undercoating			Auton						
Exterior Fastening	E E" Dottom Ext	union Hoovy Duty Tr	VHB Bonded uck Body Top Extrusi	,	ıminum Doof Corner	Ctainless Ctasl			
Exterior Trim	5.5 BULLOIN EXT		ack Body Top Extrasi Radius Corners, Stair			s, Stailliess Steel			
Stone Guard			24"	·	,				
Rear Spoiler				I Flare with Taper					
Roof				less Aluminum					
Roof Cap			•	ss Steel					
Interior Walls				, Engineered Wood					
Interior Trim				m Wall Transitions					
Ceiling		Insulation, Vinyl	Ceiling Transitions, V	hite Vinyl Liner with	Aluminum Coves				
Flooring		· ,	•	eered Wood					
Interior Lights				l" LED					







	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34	
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V						
Cargo Control	(4) 5000 lb. Recessed D-Rings						
Connector Plug	Round 7-pin Blade						
Exterior Lights	(2) Rear LE	D Loading, (4) Additi	onal Stop/Turn/Tail, F	ull LED, DOT Comp	liant, Integrated Backı	ıp/Taillights	
HVAC	Bracing and Wire for HVAC						





	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34		
Model #	FI10226VLFBRT-210	FI10228VLFBRT-210	FI10230VLFBRT-210	FI10232VLFBRT-210	FI10234VLFBRT-210		
CAPACITIES							
GVWR (lbs)			21000				
GAWR (lbs/axle)			7000				
CHASSIS							
Frame			8" x 2" Steel Tube				
Tongue		12" Ex	tension, 8" x 2" Steel Trip	e Tube			
Crossmembers		F	ormed Steel, 16" On-Cent	er			
Coupler			2-5/16" Adjustable				
Safety Chains			DOT Compliant				
Tongue Jack			12K Drop Leg, Set-Back				
Wall Studs			Steel Tube, 16" On-Cente	•			
Roof Bows			Steel Tube, 16" On-Cente	r			
Front Profile			Flat				
Beavertail			48"				
Ramp(s)	16	Extension with Bullnos	e Cap, (2) Recessed Cam	Locks, 4000 lb. with Ass	ist		
Side Door		18" Aluminum Pull-Out St	tep, 48" Wide Flush Lock,	Cast Aluminum Holdbacl	(
Vents		(1) I	Manual Roof, Sidewall Air	flow			
Fenders			Extruded Aluminum				
Axle		(3) 7000 lb. To	orsion Brake, Spread Axle	Configuration			
Hubs			Easy Lube				
Breakaway		В	attery, Switch, and Lanya	rd			
Tires			ST235/80R16E 10-PR				
Wheels			16", 8-Hole Aluminum				
Exterior Finish			.040" Aluminum				
Undercoating			Automotive				
Exterior Fastening			VHB Bonded (Screwless)				
Exterior Trim	5.5" Bottom Extrusion		y Top Extrusion, Polished Corners, Stainless Steel Ro		ners, Stainless Steel		
Stone Guard		Radius C	24" ATP	eai 1100p			
Rear Spoiler		6" St	tainless Steel Flare with T	aner			
Roof			at Top Seamless Aluminu	•			
Roof Cap			Stainless Steel	•••			
Interior Walls		Alumi	num Overlay, Engineered	Wood			
Interior Trim			ded Aluminum Wall Trans				
Ceiling			ransitions, White Vinyl Li		3		
Flooring		, , , · · · · · · · · · · · · · · · · ·	3/4" Engineered Wood				
Interior Lights			(2) 11" LED				
Switches		(1) Top Fuel Don	ne Light, 12V, (1) Top Fuel	Load Light, 12V			







	8.5 x 26	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34			
Cargo Control	(4) 5000 lb. Recessed D-Rings							
Connector Plug	Round 7-pin Blade							
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights							
HVAC	Bracing and Wire for HVAC							





	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26				
Model #	FI10220VLFBRT-070	FI10222VLFBRT-070	FI10224VLFBRT-070	FI10226VLFBRT-070				
CAPACITIES								
GVWR (lbs)		70	nn					
GAWR (lbs/axle)		35						
CHASSIS		3300						
		ć!! 0!! 0.	1 = 1					
Frame		6" x 2" St						
Tongue		12" Extension, 6" x 2	•					
Crossmembers		Formed Steel,						
Coupler		2-5/16" A	•					
Safety Chains		DOT Coi 2K Set	•					
Tongue Jack Wall Studs		Steel Tube, 1						
Roof Bows		Steel Tube, 1						
Front Profile		Steel Tube, T						
Beavertail		48						
Ramp(s)	16" Fyter	nsion with Bullnose Cap, (2) Rec		th Assist				
Side Door		• • • • • • • • • • • • • • • • • • • •						
Vents	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback (1) Manual Roof, Sidewall Airflow							
Fenders		Extruded A						
Axle		(2) 3500 lb. Torsion Brake,						
Hubs		Easy	•					
Breakaway		Battery, Switch						
Tires		ST205/75F	R15C 6-PR					
Wheels		15", 5-Hole	Aluminum					
Exterior Finish		.040" Alı	uminum					
Undercoating		Autom	notive					
Exterior Fastening		VHB Bonded	(Screwless)					
Exterior Trim	5.5" Bottom Extrusion, Hea	vy Duty Truck Body Top Extrusio	on, Polished Cast Aluminum Ro	oof Corners, Stainless Steel				
EAGING TIME		Radius Corners, Stain	•					
Stone Guard		24" /						
Rear Spoiler		6" Stainless Steel	•					
Roof		Flat Top Seaml						
Roof Cap		Stainles						
Interior Walls		Aluminum Overlay,	•					
Interior Trim		Extruded Aluminur						
Ceiling	Insulati	on, Vinyl Ceiling Transitions, W	•	Coves				
Flooring		3/4" Engine						
Interior Lights		(2) 11						
Switches		(1) Top Fuel Dome Light, 12V,	(1) Top Fuel Load Light, 12V					







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26			
Cargo Control	(4) 5000 lb. Recessed D-Rings						
Connector Plug	Round 7-pin Blade						
Exterior Lights	(2) Rear LED Loading,	(4) Additional Stop/Turn/Tail, I	Full LED, DOT Compliant, Integr	ated Backup/Taillights			
HVAC	Bracing and Wire for HVAC						







	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30		
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V							
Cargo Control	(4) 5000 lb. Recessed D-Rings							
Connector Plug	Round 7-pin Blade							
Exterior Lights	(2) Rear LE	D Loading, (4) Additio	onal Stop/Turn/Tail, F	ull LED, DOT Compl	iant, Integrated Backı	up/Taillights		
HVAC	Bracing and Wire for HVAC							





	8.5 x 32	8.5 x 34	
Model #	FI10232VLFBRT-100	FI10234VLFBRT-100	
CAPACITIES			
	0000		
GVWR (lbs)	9900		
GAWR (lbs/axle)	5000		
CHASSIS			
Frame	8" x 2" Steel Tube		
Tongue	12" Extension, 8" x 2" Steel Triple Tube		
Crossmembers	Formed Steel, 16" On-Center		
Coupler	2-5/16" Adjustable		
Safety Chains	DOT Compliant		
Tongue Jack	5K Set-Back		
Wall Studs	Steel Tube, 16" On-Center		
Roof Bows	Steel Tube, 16" On-Center		
Front Profile	Flat		
Beavertail	48"		
Ramp(s)	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist		
Side Door	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback		
Vents	(1) Manual Roof, Sidewall Airflow		
Fenders	Extruded Aluminum		
Axle	(2) 5200 lb. Torsion Brake, Spread Axle Configuration		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Aluminum		
Exterior Finish	.040" Aluminum		
Undercoating	Automotive		
Exterior Fastening		d (Screwless)	
Exterior Trim		ion, Polished Cast Aluminum Roof Corners, Stainless Steel	
	Radius Corners, Stainless Steel Rear Hoop		
Stone Guard	24" ATP		
Rear Spoiler	6" Stainless Steel Flare with Taper		
Roof Cap	Flat Top Seamless Aluminum		
Interior Walls	Stainless Steel		
Interior waiis	Aluminum Overlay, Engineered Wood Extruded Aluminum Wall Transitions		
Ceiling			
Flooring	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves 3/4" Engineered Wood		
Interior Lights	(2) 11" LED		
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V		
Cargo Control			
Caryo Cuntru	(4) 5000 lb. Recessed D-Rings		







	8.5 x 32	8.5 x 34
Connector Plug	Round 7-pin Blade	
Exterior Lights	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights	
HVAC	Bracing and Wire for HVAC	

