



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 10K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Model #</b>	F110228VLFBGNRT-100	F110230VLFBGNRT-100	F110232VLFBGNRT-100	F110234VLFBGNRT-100
<b>CAPACITIES</b>				
<b>GVWR (lbs)</b>	9900			
<b>GAWR (lbs/axle)</b>	5000			
<b>CHASSIS</b>				
<b>Frame</b>	8" x 2" Steel Tube			
<b>Tongue</b>	Gooseneck			
<b>Crossmembers</b>	Formed Steel, 16" On-Center			
<b>Coupler</b>	2-5/16" Gooseneck			
<b>Safety Chains</b>	DOT Compliant			
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear			
<b>Wall Studs</b>	Steel Tube, 16" On-Center			
<b>Roof Bows</b>	Steel Tube, 16" On-Center			
<b>Front Profile</b>	Flat			
<b>Beavertail</b>	48"			
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
<b>Access Doors</b>	16" x 48" in Riser			
<b>Vents</b>	Sidewall Airflow			
<b>Fenders</b>	Extruded Aluminum			
<b>Axle</b>	(2) 5200 lb. Torsion Brake, Spread Axle Configuration			
<b>Hubs</b>	Easy Lube			
<b>Breakaway</b>	Battery, Switch, and Lanyard			
<b>Tires</b>	ST225/75R15D 8-PR			
<b>Wheels</b>	15", 6-Hole Aluminum			
<b>Exterior Finish</b>	.040" Aluminum			
<b>Undercoating</b>	Automotive			
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
<b>Roof</b>	Flat Top Seamless Aluminum			
<b>Roof Cap</b>	Stainless Steel			
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood			
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
<b>Flooring</b>	3/4" Engineered Wood			
<b>Interior Lights</b>	(2) 11" LED			
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 14K**

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Model #</b>	F110228VLFBNRT-140	F110230VLFBNRT-140	F110232VLFBNRT-140	F110234VLFBNRT-140
<b>CAPACITIES</b>				
<b>GVWR (lbs)</b>	14000			
<b>GAWR (lbs/axle)</b>	5000			
<b>CHASSIS</b>				
<b>Frame</b>	8" x 2" Steel Tube			
<b>Tongue</b>	Gooseneck			
<b>Crossmembers</b>	Formed Steel, 16" On-Center			
<b>Coupler</b>	2-5/16" Gooseneck			
<b>Safety Chains</b>	DOT Compliant			
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear			
<b>Wall Studs</b>	Steel Tube, 16" On-Center			
<b>Roof Bows</b>	Steel Tube, 16" On-Center			
<b>Front Profile</b>	Flat			
<b>Beavertail</b>	48"			
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
<b>Access Doors</b>	16" x 48" in Riser			
<b>Vents</b>	Sidewall Airflow			
<b>Fenders</b>	Extruded Aluminum			
<b>Axle</b>	(2) 7000 lb. Torsion Brake, Spread Axle Configuration			
<b>Hubs</b>	Easy Lube			
<b>Breakaway</b>	Battery, Switch, and Lanyard			
<b>Tires</b>	ST235/80R16E 10-PR			
<b>Wheels</b>	16", 8-Hole Aluminum			
<b>Exterior Finish</b>	.040" Aluminum			
<b>Undercoating</b>	Automotive			
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
<b>Roof</b>	Flat Top Seamless Aluminum			
<b>Roof Cap</b>	Stainless Steel			
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood			
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
<b>Flooring</b>	3/4" Engineered Wood			
<b>Interior Lights</b>	(2) 11" LED			
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Connector Plug</b>	Round 7-pin Blade			
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
<b>HVAC</b>	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 15K**

	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38
<b>Model #</b>	FI10230VLFBGNRT-150	FI10232VLFBGNRT-150	FI10234VLFBGNRT-150	FI10236VLFBGNRT-150	FI10238VLFBGNRT-150
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	15000				
<b>GAWR (lbs/axle)</b>	5000				
<b>CHASSIS</b>					
<b>Frame</b>	8" x 2" Steel Tube				
<b>Tongue</b>	Gooseneck				
<b>Crossmembers</b>	Formed Steel, 16" On-Center				
<b>Coupler</b>	2-5/16" Gooseneck				
<b>Safety Chains</b>	DOT Compliant				
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear				
<b>Wall Studs</b>	Steel Tube, 16" On-Center				
<b>Roof Bows</b>	Steel Tube, 16" On-Center				
<b>Front Profile</b>	Flat				
<b>Beavertail</b>	48"				
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist				
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback				
<b>Access Doors</b>	16" x 48" in Riser				
<b>Vents</b>	Sidewall Airflow				
<b>Fenders</b>	Extruded Aluminum				
<b>Axle</b>	(3) 5200 lb. Torsion Brake, Spread Axle Configuration				
<b>Hubs</b>	Easy Lube				
<b>Breakaway</b>	Battery, Switch, and Lanyard				
<b>Tires</b>	ST225/75R15D 8-PR				
<b>Wheels</b>	15", 6-Hole Aluminum				
<b>Exterior Finish</b>	.040" Aluminum				
<b>Undercoating</b>	Automotive				
<b>Exterior Fastening</b>	VHB Bonded (Screwless)				
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop				
<b>Roof</b>	Flat Top Seamless Aluminum				
<b>Roof Cap</b>	Stainless Steel				
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood				
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions				
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves				
<b>Flooring</b>	3/4" Engineered Wood				
<b>Interior Lights</b>	(2) 11" LED				
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 15K

	8.5 x 30	8.5 x 32	8.5 x 34	8.5 x 36	8.5 x 38
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings				
<b>Connector Plug</b>	Round 7-pin Blade				
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights				
<b>HVAC</b>	Bracing and Wire for HVAC				



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



## AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Model #</b>	F110228VLFBGNRT-160	F110230VLFBGNRT-160	F110232VLFBGNRT-160	F110234VLFBGNRT-160
<b>CAPACITIES</b>				
<b>GVWR (lbs)</b>	16000			
<b>GAWR (lbs/axle)</b>	8000			
<b>CHASSIS</b>				
<b>Frame</b>	8" x 2" Steel Tube			
<b>Tongue</b>	Gooseneck			
<b>Crossmembers</b>	Formed Steel, 16" On-Center			
<b>Coupler</b>	2-5/16" Gooseneck			
<b>Safety Chains</b>	DOT Compliant			
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear			
<b>Wall Studs</b>	Steel Tube, 16" On-Center			
<b>Roof Bows</b>	Steel Tube, 16" On-Center			
<b>Front Profile</b>	Flat			
<b>Beavertail</b>	48"			
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist			
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback			
<b>Access Doors</b>	16" x 48" in Riser			
<b>Vents</b>	Sidewall Airflow			
<b>Fenders</b>	Extruded Aluminum			
<b>Axle</b>	(2) 8000 lb. Torsion Brake, Spread Axle Configuration			
<b>Hubs</b>	Oil Bath			
<b>Breakaway</b>	Battery, Switch, and Lanyard			
<b>Tires</b>	215/75R17.5J 18-PR			
<b>Wheels</b>	17.5", 8-Hole Aluminum			
<b>Exterior Finish</b>	.040" Aluminum			
<b>Undercoating</b>	Automotive			
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop			
<b>Roof</b>	Flat Top Seamless Aluminum			
<b>Roof Cap</b>	Stainless Steel			
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood			
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves			
<b>Flooring</b>	3/4" Engineered Wood			
<b>Interior Lights</b>	(2) 11" LED			
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Connector Plug</b>	Round 7-pin Blade			
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
<b>HVAC</b>	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 21K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
<b>Model #</b>	FI10240VLFBGNRT-210	FI10242VLFBGNRT-210	FI10244VLFBGNRT-210	FI10246VLFBGNRT-210	FI10248VLFBGNRT-210	FI10250VLFBGNRT-210
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	21000					
<b>GAWR (lbs/axle)</b>	7000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	Gooseneck					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Gooseneck					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Flat					
<b>Beavertail</b>	48"					
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
<b>Access Doors</b>	16" x 48" in Riser					
<b>Vents</b>	Sidewall Airflow					
<b>Fenders</b>	Extruded Aluminum					
<b>Axle</b>	(3) 7000 lb. Torsion Brake, Spread Axle Configuration					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST235/80R16E 10-PR					
<b>Wheels</b>	16", 8-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Roof Cap</b>	Stainless Steel					
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) 11" LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.







**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 21K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>HVAC</b>	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 21K**

**8.5 x 52**

<b>Model #</b>	FI10252VLFBNRT-210
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	21000
<b>GAWR (lbs/axle)</b>	7000
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	Gooseneck
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Coupler</b>	2-5/16" Gooseneck
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	Flat
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
<b>Access Doors</b>	16" x 48" in Riser
<b>Vents</b>	Sidewall Airflow
<b>Fenders</b>	Extruded Aluminum
<b>Axle</b>	(3) 7000 lb. Torsion Brake, Spread Axle Configuration
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST235/80R16E 10-PR
<b>Wheels</b>	16", 8-Hole Aluminum
<b>Exterior Finish</b>	.040" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Roof Cap</b>	Stainless Steel
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) 11" LED
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 21K**

**8.5 x 52**

**HVAC**

**Bracing and Wire for HVAC**



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 24K**

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
<b>Model #</b>	FI10240VLFBGNRT-240	FI10242VLFBGNRT-240	FI10244VLFBGNRT-240	FI10246VLFBGNRT-240	FI10248VLFBGNRT-240	FI10250VLFBGNRT-240
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	24000					
<b>GAWR (lbs/axle)</b>	8000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	Gooseneck					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Gooseneck					
<b>Safety Chains</b>	DOT Compliant					
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Flat					
<b>Beavertail</b>	48"					
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist					
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback					
<b>Access Doors</b>	16" x 48" in Riser					
<b>Vents</b>	Sidewall Airflow					
<b>Fenders</b>	Extruded Aluminum					
<b>Axle</b>	(3) 8000 lb. Torsion Brake, Spread Axle Configuration					
<b>Hubs</b>	Oil Bath					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	215/75R17.5J 18-PR					
<b>Wheels</b>	17.5", 8-Hole Aluminum					
<b>Exterior Finish</b>	.040" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Roof Cap</b>	Stainless Steel					
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) 11" LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 24K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
<b>Connector Plug</b>	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights					
<b>HVAC</b>	Bracing and Wire for HVAC					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 24K**

**8.5 x 52**

<b>Model #</b>	F110252VLFBNRT-240
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	24000
<b>GAWR (lbs/axle)</b>	8000
<b>CHASSIS</b>	
<b>Frame</b>	8" x 2" Steel Tube
<b>Tongue</b>	Gooseneck
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Coupler</b>	2-5/16" Gooseneck
<b>Safety Chains</b>	DOT Compliant
<b>Tongue Jack</b>	Dual 12K, 2-Speed Landing Gear
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	Flat
<b>Beavertail</b>	48"
<b>Ramp(s)</b>	16" Extension with Bullnose Cap, (2) Recessed Cam Locks, 4000 lb. with Assist
<b>Side Door</b>	48" Aluminum Pull-Out Step, 48" Wide Flush Lock, Cast Aluminum Holdback
<b>Access Doors</b>	16" x 48" in Riser
<b>Vents</b>	Sidewall Airflow
<b>Fenders</b>	Extruded Aluminum
<b>Axle</b>	(3) 8000 lb. Torsion Brake, Spread Axle Configuration
<b>Hubs</b>	Oil Bath
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	215/75R17.5J 18-PR
<b>Wheels</b>	17.5", 8-Hole Aluminum
<b>Exterior Finish</b>	.040" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	5.5" Bottom Extrusion, ATP Riser Wall, Heavy Duty Truck Body Top Extrusion, Polished Cast Aluminum Roof Corners, Stainless Steel Radius Corners, Stainless Steel Rear Hoop
<b>Roof</b>	Flat Top Seamless Aluminum
<b>Roof Cap</b>	Stainless Steel
<b>Interior Walls</b>	Aluminum Overlay, Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	Insulation, Vinyl Ceiling Transitions, White Vinyl Liner with Aluminum Coves
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) 11" LED
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Round 7-pin Blade
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**AFTERSHOCK GOOSENECK RACE  
AFTERSHOCK FLAT TOP FLAT FRONT 24K**

8.5 x 52

HVAC

Bracing and Wire for HVAC



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# AFTERSHOCK GOOSENECK RACE AFTERSHOCK FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
<b>Connector Plug</b>	Round 7-pin Blade			
<b>Exterior Lights</b>	(2) Rear LED Loading, (4) Additional Stop/Turn/Tail, Full LED, DOT Compliant, Integrated Backup/Taillights			
<b>HVAC</b>	Bracing and Wire for HVAC			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.