

	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12		
Model #	FI8412CDFB-100	FI8414CDFB-	FI8416CDFB-	FI8418CDFB-	FI8420CDFB-	FI10212CDFB-100		
Wouei #	F10412CDFB-100	100	100	100	100	FIIUZIZGDFB-100		
CAPACITIES								
GVWR (lbs)			99	900				
GAWR (lbs/axle)			5(	000				
CHASSIS								
Frame		6" x 2" Steel Tube						
Tongue			6" Extension, 6" x	2" Steel Triple Tul	oe .			
Crossmembers			Formed Steel	, 16" On-Center				
Integrated Step(s)						Interior Recessed		
Coupler			2-5/16" /	Adjustable				
Safety Chains			DOT Co	ompliant				
Tongue Jack		7K Drop Le	g, Frame Mounted	, 7K Drop Leg, Fra	me Mounted			
Wall Studs		Steel Tube, 16" On-Center						
Roof Bows	Steel Tube, 8" On-Center							
Front Profile	Flat							
Stabilizers	Rear Drop-Leg Jacks							
Rear Door		Barn-Style Double with Cambar and Step Bumper						
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders		Aluminum Treadplate						
Axle				Torsion Brake				
Hubs		Easy Lube						
Breakaway		Battery, Switch, and Lanyard						
Tires		ST225/75R15D 8-PR						
Wheels		15", 6-	Hole Steel, Cente	•	Rings1			
Exterior Finish				luminum				
Undercoating				motive				
Exterior Fastening	0 7" P			d (Screwless)				
Exterior Trim	2.7" Botton	n Extrusion, 2.7" 10	•		ers, Color Matchir	ig Rear Hoop		
Stone Guard				ATP				
Roof			Flat Top Seam	less Aluminum	adday Daalsa with	(4) Haarii Distri Laddar		
Exterior Storage	(4) Heavy Duty L	adder Racks with I	Rear Roller	``	adder Racks with Roller	(4) Heavy Duty Ladder Racks with Rear Roller		
<b>Exterior Accessories</b>		ATP and Eng	ineered Wood Ton	gue Cover, Front A	Access Ladder			
Interior Walls			Enginee	red Wood				
Interior Trim			Vinyl Wall	Transitions				
Interior Lights		(	1) LED, (2) 48" 11	OV Wrap Around L	ED			
Switches		(1) 110V, (2) Pa	air Top Fuel 3-Way	, 12V, (2) Pair Top	Fuel 3-Way, 12V			



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

© 2025 Novae LLC





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12
Fixtures	(2) Tool Cabinets with Aluminum Work Station	` '	s with Aluminum Station	` '	s with Aluminum Station	(2) Tool Cabinets with Aluminum Work Station
Cargo Control	(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row					
Connector Plug	Round 7-pin Blade					
<b>Exterior Lights</b>	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Recep	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles				





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20				
Model #	FI10214CDFB-100	FI10216CDFB-100	FI10218CDFB-100	FI10220CDFB-100				
CAPACITIES								
GVWR (lbs)		99	00					
GAWR (lbs/axle)		50	00					
CHASSIS								
rame	6" x 2" Steel Tube							
<b>Tongue</b>		6" Extension, 6" x 2	2" Steel Triple Tube					
Crossmembers		Formed Steel,	16" On-Center					
Integrated Step(s)		Interior F	Recessed					
Coupler		2-5/16" A	djustable					
Safety Chains		DOT Co	mpliant					
ongue Jack		7K Drop Leg, Frame Mounted	7K Drop Leg, Frame Mounted					
Wall Studs		Steel Tube, 1	6" On-Center					
Roof Bows		Steel Tube,	B" On-Center					
ront Profile		Fl	at					
Stabilizers		Rear Drop	Leg Jacks					
Rear Door		Barn-Style Double with (	Cambar and Step Bumper					
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
/ents	Roof Vent Frame, Salem Sidewall Airflow							
enders	Aluminum Treadplate							
\xle	(2) 5200 lb. Torsion Brake							
lubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard							
lires lines	ST225/75R15D 8-PR							
Vheels	15", 6-Hole Steel, Center Caps and Beauty Rings1							
xterior Finish		.030" Al	uminum					
Indercoating		Autor	notive					
Exterior Fastening		VHB Bonded	(Screwless)					
Exterior Trim	2.7" Bottom Extr	usion, 2.7" Top Extrusion, ATP I	Radius Front Corners, Color Ma	tching Rear Hoop				
Stone Guard		24"	ATP					
Roof		Flat Top Seam	less Aluminum					
Exterior Storage	(4) Heavy Duty Ladder	Racks with Rear Roller	(5) Heavy Duty Ladder	Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Ton	gue Cover, Front Access Ladde	r				
nterior Walls		Engineer	ed Wood					
nterior Trim		Vinyl Wall	Transitions					
nterior Lights		(1) LED, (2) 48" 110	V Wrap Around LED					
Switches	(1	) 110V, (2) Pair Top Fuel 3-Way,	12V, (2) Pair Top Fuel 3-Way, 1	2V				
Fixtures	(3) Tool Cabinets with	Aluminum Work Station	(4) Tool Cabinets with	Aluminum Work Station				
Cargo Control	(	4) 5000 lb. Recessed D-Rings,	Recessed Wall E-Track, One Ro	w				
Connector Plug		Round 7-	pin Blade					







	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
<b>Exterior Lights</b>	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					





	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	
Model #	FIG.412CDFD 070	FI8414CDFB-	FI8416CDFB-	FI8418CDFB-	FI8420CDFB-	FI10212CDFD 070	
Model #	FI8412CDFB-070	070	070	070	070	FI10212CDFB-070	
CAPACITIES							
GVWR (lbs)			7	000			
GAWR (lbs/axle)	3500						
CHASSIS							
Frame	6" x 2" Steel Tube						
Tongue			6" Extension, 6" x	2" Steel Triple Tul	ре		
Crossmembers			•	, 16" On-Center			
Integrated Step(s)						Interior Recessed	
Coupler			2-5/16"	Adjustable			
Safety Chains			DOT C	ompliant			
Tongue Jack		7K Drop Le	g, Frame Mounted	l, 7K Drop Leg, Fra	me Mounted		
Wall Studs		Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 8" On-Center						
Front Profile	Flat						
Stabilizers	Rear Drop-Leg Jacks						
Rear Door	Barn-Style Double with Cambar and Step Bumper						
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback						
Vents	Roof Vent Frame, Salem Sidewall Airflow						
Fenders	Aluminum Treadplate						
Axle	(2) 3500 lb. Torsion Brake						
Hubs	Easy Lube						
Breakaway		Battery, Switch, and Lanyard					
Tires		4-11 -		5R15C 6-PR			
Wheels		15", 5-	•	r Caps and Beauty	Rings1		
Exterior Finish				luminum			
Undercoating				motive			
Exterior Fastening Exterior Trim	2 7" Potton	a Extrucion 2.7" To		d (Screwless)	ers, Color Matchin	ng Door Hoop	
Stone Guard	Z./ BUILON	11 EXITUSION, 2.7 10	•	' ATP	icis, cuiui Matchin	iy keai noop	
Roof				nless Aluminum			
			<del>-</del>		adder Racks with	(4) Heavy Duty Ladder	
Exterior Storage	(4) Heavy Duty L	adder Racks with I	Rear Roller	1	Roller	Racks with Rear Roller	
<b>Exterior Accessories</b>		ATP and Eng	ineered Wood Tor	ngue Cover, Front A	Access Ladder		
Interior Walls			Enginee	ered Wood			
Interior Trim			Vinyl Wall	Transitions			
Interior Lights		(	1) LED, (2) 48" 11	0V Wrap Around L	ED		
Switches		(1) 110V, (2) Pa	air Top Fuel 3-Way	, 12V, (2) Pair Top	Fuel 3-Way, 12V		







	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12
Fixtures	(2) Tool Cabinets with Aluminum Work Station	` '	s with Aluminum Station	` '	s with Aluminum Station	(2) Tool Cabinets with Aluminum Work Station
Cargo Control	(4) 5000 lb. Recessed D-Rings, Recessed Wall E-Track, One Row					
Connector Plug	Round 7-pin Blade					
Exterior Lights	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Recep	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles				





	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20				
Model #	FI10214CDFB-070	FI10216CDFB-070	FI10218CDFB-070	FI10220CDFB-070				
	11102140D1 B-070	11102100010-070	11102100010-070	1110220GDI B-070				
CAPACITIES								
GVWR (lbs)			00					
GAWR (lbs/axle)	3500							
CHASSIS								
Frame	6" x 2" Steel Tube							
Tongue	6" Extension, 6" x 2" Steel Triple Tube							
Crossmembers		Formed Steel,	16" On-Center					
Integrated Step(s)		Interior I	Recessed					
Coupler		2-5/16" <i>A</i>	djustable					
Safety Chains		DOT Co	mpliant					
Tongue Jack		• •	7K Drop Leg, Frame Mounted					
Wall Studs		•	6" On-Center					
Roof Bows		·	B" On-Center					
Front Profile			at					
Stabilizers	Rear Drop-Leg Jacks							
Rear Door	Barn-Style Double with Cambar and Step Bumper							
Side Door	36" Wide Flush Lock, Additional Barlock and Hasp, Cast Aluminum Holdback							
Vents	Roof Vent Frame, Salem Sidewall Airflow							
Fenders	Aluminum Treadplate							
Axle 	(2) 3500 lb. Torsion Brake							
Hubs	Easy Lube							
Breakaway	Battery, Switch, and Lanyard ST205/75R15C 6-PR							
Tires								
Wheels Exterior Finish	15", 5-Hole Steel, Center Caps and Beauty Rings1 .030" Aluminum							
			notive					
Undercoating Exterior Fastening			(Screwless)					
Exterior Trim	2 7" Rottom Extr	usion, 2.7" Top Extrusion, ATP I	<u> </u>	atching Door Hoon				
Stone Guard	Z./ DOLLOIN EXLI	· · · · · · · · · · · · · · · · · · ·	ATP	iteming iteal Hoop				
Roof			less Aluminum					
Exterior Storage	(4) Heavy Duty I adde	Racks with Rear Roller		Racks with Rear Roller				
Exterior Accessories		ATP and Engineered Wood Ton						
Interior Walls		•	ed Wood					
Interior Trim		<u> </u>	Transitions					
Interior Lights		•	V Wrap Around LED					
Switches	(1	) 110V, (2) Pair Top Fuel 3-Way,		12V				
Fixtures	(3) Tool Cabinets with	Aluminum Work Station	(4) Tool Cabinets with	Aluminum Work Station				
Cargo Control	(	4) 5000 lb. Recessed D-Rings,	Recessed Wall E-Track, One Ro	w				
Connector Plug		Round 7-	pin Blade					







	8.5 x 14	8.5 x 16	8.5 x 18	8.5 x 20		
<b>Exterior Lights</b>	(2) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					
110v Electrical	(1) Exterior GFI Receptacle, 30 Amp, 25 ft. Power Cord, 30 Amp Motor Base Plug, 30 Amp Service Panel, (4) Interior Receptacles					

