



SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 10K

	7.5 x 12	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16
Model #	FI9012THSVA-100	FI9014THSVA-100	FI9016THSVA-100	FI9018THSVA-100	FI9020THSVA-100	FI10216THSVA-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Double Hollow Aluminum Tube					
Tongue						6" x 2" Double Hollow Aluminum Triple Tube
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop					30" Sloped V-Nose with 12" Drop
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Stone Guard	24" Sloped ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Luan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 10K

	7.5 x 12	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 10K

	8.5 x 18	8.5 x 20	8.5 x 24
Model #	FI10218THSVA-100	FI10220THSVA-100	FI10224THSVA-100
CAPACITIES			
GVWR (lbs)	9900		
GAWR (lbs/axle)	5000		
CHASSIS			
Frame	6" x 2" Double Hollow Aluminum Tube		
Tongue	6" x 2" Double Hollow Aluminum Triple Tube		
Crossmembers	Aluminum Tube, 24" On-Center		
Coupler	2-5/16" A-Frame		
Safety Chains	DOT Compliant		
Tongue Jack	2K Coupler Mounted		
Wall Studs	Aluminum Tube, 16" On-Center		
Roof Bows	Aluminum Tube, 24" On-Center		
Front Profile	30" Sloped V-Nose with 12" Drop		
Ramp(s)	12" Extension, Aluminum with Assist		
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Aluminum Treadplate		
Axle	(2) 5200 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST225/75R15D 8-PR		
Wheels	15", 6-Hole Steel		
Exterior Finish	.030" Aluminum		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop		
Stone Guard	24" Sloped ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Lauan Strip		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 3K

	6 x 10	6 x 12	6 x 14
Model #	FI7210THSVA-030	FI7212THSVA-030	FI7214THSVA-030
CAPACITIES			
GVWR (lbs)		2990	
GAWR (lbs/axle)		3500	
CHASSIS			
Frame	3" x 2" Aluminum Tube		
Tongue	4" x 2" Aluminum Tube		
Crossmembers	Aluminum Tube, 24" On-Center		
Coupler	2" A-Frame		
Safety Chains	DOT Compliant		
Tongue Jack	2K Coupler Mounted		
Wall Studs	Aluminum Tube, 16" On-Center		
Roof Bows	Aluminum Tube, 24" On-Center		
Front Profile	24" Sloped V-Nose with 12" Drop		
Ramp(s)	12" Extension, Aluminum with Assist		
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Aluminum Treadplate		
Axle	3500 lb. Drop Spring Idler		
Hubs	Easy Lube		
Tires	ST205/75R15C 6-PR		
Wheels	15", 5-Hole Steel		
Exterior Finish	.030" Aluminum		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop		
Stone Guard	24" Sloped ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Lauan Strip		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Flat 4-pin		
Exterior Lights	Full LED, DOT Compliant		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 7K

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7.5 x 12
Model #	FI7212THSVA-070	FI8412THSVA-070	FI8414THSVA-070	FI8416THSVA-070	FI8418THSVA-070	FI9012THSVA-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Double Hollow Aluminum Tube	4" x 2" Aluminum Tube				
Tongue	4" x 2" Aluminum Tube	5" x 2" Aluminum Tube, 5" x 2" Aluminum Tube				
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop					
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Stone Guard	24" Sloped ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Luan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 7K

	7.5 x 14	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 16	8.5 x 18
Model #	FI9014THSVA-070	FI9016THSVA-070	FI9018THSVA-070	FI9020THSVA-070	FI10216THSVA-070	FI10218THSVA-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	4" x 2" Aluminum Tube				6" x 2" Double Hollow Aluminum Tube	
Tongue					6" x 2" Double Hollow Aluminum Triple Tube	
Crossmembers	Aluminum Tube, 24" On-Center					
Coupler	2-5/16" A-Frame					
Safety Chains	DOT Compliant					
Tongue Jack	2K Coupler Mounted					
Wall Studs	Aluminum Tube, 16" On-Center					
Roof Bows	Aluminum Tube, 24" On-Center					
Front Profile	24" Sloped V-Nose with 12" Drop				30" Sloped V-Nose with 12" Drop	
Ramp(s)	12" Extension, Aluminum with Assist					
Side Door	32" Wide Flush Lock, Cast Aluminum Holdback				36" Wide Flush Lock, Cast Aluminum Holdback	
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Stone Guard	24" Sloped ATP					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	Lauan Strip					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE ALUMINUM CARGO SHOCKWAVE FLAT TOP V-NOSE 7K

	8.5 x 20	8.5 x 22	8.5 x 24
Model #	FI10220THSVA-070	FI10222THSVA-070	FI10224THSVA-070
CAPACITIES			
GVWR (lbs)	7000		
GAWR (lbs/axle)	3500		
CHASSIS			
Frame	6" x 2" Double Hollow Aluminum Tube		
Tongue	6" x 2" Double Hollow Aluminum Triple Tube		
Crossmembers	Aluminum Tube, 24" On-Center		
Coupler	2-5/16" A-Frame		
Safety Chains	DOT Compliant		
Tongue Jack	2K Coupler Mounted		
Wall Studs	Aluminum Tube, 16" On-Center		
Roof Bows	Aluminum Tube, 24" On-Center		
Front Profile	30" Sloped V-Nose with 12" Drop		
Ramp(s)	12" Extension, Aluminum with Assist		
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback		
Vents	Sidewall Airflow		
Fenders	Aluminum Treadplate		
Axle	(2) 3500 lb. Drop Spring Brake		
Hubs	Easy Lube		
Breakaway	Battery, Switch, and Lanyard		
Tires	ST205/75R15C 6-PR		
Wheels	15", 5-Hole Steel		
Exterior Finish	.030" Aluminum		
Exterior Fastening	VHB Bonded (Screwless)		
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop		
Stone Guard	24" Sloped ATP		
Roof	Flat Top Seamless Aluminum		
Interior Walls	Engineered Wood		
Interior Trim	Extruded Aluminum Wall Transitions		
Ceiling	Lauan Strip		
Flooring	3/4" Engineered Wood		
Interior Lights	(2) LED		
Switches	(1) Dome Light, 12V		
Connector Plug	Round 7-pin Blade		
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

