



SHOCKWAVE GOOSENECK CARGO SHOCKWAVE FLAT TOP FLAT FRONT 10K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	FI10228THFBGN-100	FI10230THFBGN-100	FI10232THFBGN-100	FI10234THFBGN-100
CAPACITIES				
GVWR (lbs)	9900			
GAWR (lbs/axle)	5000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Aluminum Treadplate			
Axle	(2) 5200 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Wheels	15", 6-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Connector Plug	Round 7-pin Blade			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE GOOSENECK CARGO SHOCKWAVE FLAT TOP FLAT FRONT 14K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	FI10228THFBGN-140	FI10230THFBGN-140	FI10232THFBGN-140	FI10234THFBGN-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Aluminum Treadplate			
Axle	(2) 7000 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Wheels	16", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Connector Plug	Round 7-pin Blade			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE GOOSENECK CARGO
SHOCKWAVE FLAT TOP FLAT FRONT 15K**

	8.5 x 36	8.5 x 38
Model #	F110236THFBGN-150	F110238THFBGN-150
CAPACITIES		
GVWR (lbs)	15000	
GAWR (lbs/axle)	5000	
CHASSIS		
Frame	8" x 2" Steel Tube	
Tongue	Gooseneck	
Crossmembers	Formed Steel, 16" On-Center	
Integrated Step(s)	Interior Recessed	
Coupler	2-5/16" Gooseneck	
Safety Chains	DOT Compliant	
Tongue Jack	Dual 12K, 2-Speed Landing Gear	
Wall Studs	Steel Tube, 16" On-Center	
Roof Bows	Steel Tube, 16" On-Center	
Front Profile	Flat	
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist	
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback	
Access Doors	16" x 48" in Riser	
Vents	Sidewall Airflow	
Fenders	Aluminum Treadplate	
Axle	(3) 5200 lb. Drop Spring Brake	
Hubs	Easy Lube	
Breakaway	Battery, Switch, and Lanyard	
Wheels	15", 6-Hole Aluminum	
Exterior Finish	.030" Aluminum	
Undercoating	Automotive	
Exterior Fastening	VHB Bonded (Screwless)	
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop	
Roof	Flat Top Seamless Aluminum	
Interior Walls	Engineered Wood	
Interior Trim	Extruded Aluminum Wall Transitions	
Ceiling	White Vinyl Liner with Aluminum Coves	
Flooring	3/4" Engineered Wood	
Interior Lights	(2) LED	
Switches	(1) Dome Light, 12V	
Connector Plug	Round 7-pin Blade	
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE GOOSENECK CARGO SHOCKWAVE FLAT TOP FLAT FRONT 16K

	8.5 x 28	8.5 x 30	8.5 x 32	8.5 x 34
Model #	FI10228THFBGN-160	FI10230THFBGN-160	FI10232THFBGN-160	FI10234THFBGN-160
CAPACITIES				
GVWR (lbs)	16000			
GAWR (lbs/axle)	8000			
CHASSIS				
Frame	8" x 2" Steel Tube			
Tongue	Gooseneck			
Crossmembers	Formed Steel, 16" On-Center			
Integrated Step(s)	Interior Recessed			
Coupler	2-5/16" Gooseneck			
Safety Chains	DOT Compliant			
Tongue Jack	Dual 12K, 2-Speed Landing Gear			
Wall Studs	Steel Tube, 16" On-Center			
Roof Bows	Steel Tube, 16" On-Center			
Front Profile	Flat			
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist			
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback			
Access Doors	16" x 48" in Riser			
Vents	Sidewall Airflow			
Fenders	Aluminum Treadplate			
Axle	(2) 8000 lb. Drop Spring Brake			
Hubs	Oil Bath			
Breakaway	Battery, Switch, and Lanyard			
Wheels	17.5", 8-Hole Aluminum			
Exterior Finish	.030" Aluminum			
Undercoating	Automotive			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop			
Roof	Flat Top Seamless Aluminum			
Interior Walls	Engineered Wood			
Interior Trim	Extruded Aluminum Wall Transitions			
Ceiling	White Vinyl Liner with Aluminum Coves			
Flooring	3/4" Engineered Wood			
Interior Lights	(2) LED			
Switches	(1) Dome Light, 12V			
Connector Plug	Round 7-pin Blade			
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE GOOSENECK CARGO SHOCKWAVE FLAT TOP FLAT FRONT 21K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	FI10240THFBGN-210	FI10242THFBGN-210	FI10244THFBGN-210	FI10246THFBGN-210	FI10248THFBGN-210	FI10250THFBGN-210
CAPACITIES						
GVWR (lbs)	21000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(3) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Wheels	16", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE GOOSENECK CARGO
SHOCKWAVE FLAT TOP FLAT FRONT 21K**

8.5 x 52

Model #	FI10252THFBGN-210
CAPACITIES	
GVWR (lbs)	21000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(3) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Wheels	16", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE GOOSENECK CARGO SHOCKWAVE FLAT TOP FLAT FRONT 24K

	8.5 x 40	8.5 x 42	8.5 x 44	8.5 x 46	8.5 x 48	8.5 x 50
Model #	FI10240THFBGN-240	FI10242THFBGN-240	FI10244THFBGN-240	FI10246THFBGN-240	FI10248THFBGN-240	FI10250THFBGN-240
CAPACITIES						
GVWR (lbs)	24000					
GAWR (lbs/axle)	8000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	Gooseneck					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Gooseneck					
Safety Chains	DOT Compliant					
Tongue Jack	Dual 12K, 2-Speed Landing Gear					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Flat					
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Access Doors	16" x 48" in Riser					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(3) 8000 lb. Drop Spring Brake, (3) 8000 lb. Drop Spring Brake					
Hubs	Oil Bath					
Breakaway	Battery, Switch, and Lanyard					
Wheels	17.5", 8-Hole Aluminum					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White Vinyl Liner with Aluminum Coves					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Dome Light, 12V					
Connector Plug	Round 7-pin Blade					
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE GOOSENECK CARGO
SHOCKWAVE FLAT TOP FLAT FRONT 24K**

8.5 x 52

Model #	FI10252THFBGN-240
CAPACITIES	
GVWR (lbs)	24000
GAWR (lbs/axle)	8000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	Gooseneck
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Gooseneck
Safety Chains	DOT Compliant
Tongue Jack	Dual 12K, 2-Speed Landing Gear
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Flat
Ramp(s)	12" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Access Doors	16" x 48" in Riser
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(3) 8000 lb. Drop Spring Brake, (3) 8000 lb. Drop Spring Brake
Hubs	Oil Bath
Breakaway	Battery, Switch, and Lanyard
Wheels	17.5", 8-Hole Aluminum
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Riser Wall, Brite Aluminum Rear Hoop
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White Vinyl Liner with Aluminum Coves
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Connector Plug	Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

