



SHOCKWAVE CAR HAULER

SHOCKWAVE ROUND TOP ROUND FRONT 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216THRFBH-070	FI10218THRFBH-070	FI10220THRFBH-070	FI10222THRFBH-070	FI10224THRFBH-070	FI10226THRFBH-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Round					
Beavertail	32"			48"		
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Round Top Seamless Aluminum					
Roof Cap	TPO					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER SHOCKWAVE ROUND TOP ROUND FRONT 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE ROUND TOP ROUND FRONT 7K

8.5 x 28

Model #	FI10228THRFCH-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Round
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Aluminum, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
Stone Guard	24" ATP
Roof	Round Top Seamless Aluminum
Roof Cap	TPO
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER
SHOCKWAVE ROUND TOP ROUND FRONT 7K

8.5 x 28

Exterior Lights

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216THSVCH-100	FI10218THSVCH-100	FI10220THSVCH-100	FI10222THSVCH-100	FI10224THSVCH-100	FI10226THSVCH-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Sloped V-Nose with 12" Drop					
Beavertail	32"			48"		
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" Sloped ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K

8.5 x 28

Model #	FI10228THSVCH-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Aluminum, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Stone Guard	24" Sloped ATP
Rear Spoiler	9" Brite Aluminum Flare
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K

8.5 x 28

Exterior Lights

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER

SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216THSVCH-140	FI10218THSVCH-140	FI10220THSVCH-140	FI10222THSVCH-140	FI10224THSVCH-140	FI10226THSVCH-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
CHASSIS						
Frame	8" x 2" Steel Tube					
Tongue	6" Extension, 8" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue					
Tongue Jack	7K Drop Leg, Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Sloped V-Nose with 12" Drop					
Beavertail	32"			48"		
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 7000 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST235/80R16E 10-PR					
Wheels	16", 8-Hole Aluminum, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" Sloped ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K

8.5 x 28

Model #	FI10228THSVCH-140
CAPACITIES	
GVWR (lbs)	14000
GAWR (lbs/axle)	7000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	7K Drop Leg, Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 7000 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST235/80R16E 10-PR
Wheels	16", 8-Hole Aluminum, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Stone Guard	24" Sloped ATP
Rear Spoiler	9" Brite Aluminum Flare
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K

8.5 x 28

Exterior Lights

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER

SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216THSVCH-070	FI10218THSVCH-070	FI10220THSVCH-070	FI10222THSVCH-070	FI10224THSVCH-070	FI10226THSVCH-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	30" Sloped V-Nose with 12" Drop					
Beavertail	32"			48"		
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Aluminum, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop					
Stone Guard	24" Sloped ATP					
Rear Spoiler	9" Brite Aluminum Flare					
Roof	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

8.5 x 28

Model #	FI10228THSVCH-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Aluminum, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, Brite Aluminum Nose Cap, Brite Aluminum Rear Hoop
Stone Guard	24" Sloped ATP
Rear Spoiler	9" Brite Aluminum Flare
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CAR HAULER
SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K**

8.5 x 28

Exterior Lights

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER

SHOCKWAVE ROUND TOP ROUND FRONT 10K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216THRFBH-100	FI10218THRFBH-100	FI10220THRFBH-100	FI10222THRFBH-100	FI10224THRFBH-100	FI10226THRFBH-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5000					
CHASSIS						
Frame	6" x 2" Steel Tube					
Tongue	6" Extension, 6" x 2" Steel Triple Tube					
Crossmembers	Formed Steel, 16" On-Center					
Integrated Step(s)	Interior Recessed					
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue					
Tongue Jack	2K Set-Back					
Wall Studs	Steel Tube, 16" On-Center					
Roof Bows	Steel Tube, 16" On-Center					
Front Profile	Round					
Beavertail	32"			48"		
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 5200 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST225/75R15D 8-PR					
Wheels	15", 6-Hole Aluminum, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
Stone Guard	24" ATP					
Roof	Round Top Seamless Aluminum					
Roof Cap	TPO					
Interior Walls	Engineered Wood					
Interior Trim	Extruded Aluminum Wall Transitions					
Ceiling	White ThermoPly®					
Flooring	3/4" Engineered Wood					
Interior Lights	(2) LED					
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER SHOCKWAVE ROUND TOP ROUND FRONT 10K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Cargo Control	(4) 5000 lb. Recessed D-Rings					
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
Exterior Lights	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



SHOCKWAVE CAR HAULER
SHOCKWAVE ROUND TOP ROUND FRONT 10K

8.5 x 28

Model #	FI10228THRFCH-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	6" Extension, 8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Set-Back
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	Round
Beavertail	48"
Ramp(s)	16" Extension with Bullnose Cap, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Cast Aluminum Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Aluminum, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
Stone Guard	24" ATP
Roof	Round Top Seamless Aluminum
Roof Cap	TPO
Interior Walls	Engineered Wood
Interior Trim	Extruded Aluminum Wall Transitions
Ceiling	White ThermoPly®
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CAR HAULER
SHOCKWAVE ROUND TOP ROUND FRONT 10K

8.5 x 28

Exterior Lights

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.