



# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 10K

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	8.5 x 14
<b>Model #</b>	F18414THRF-100	F18416THRF-100	F18418THRF-100	F18420THRF-100	F110212THRF-100	F110214THRF-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Tube				6" Extension, 6" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>					Interior Recessed	
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Round					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist				12" Extension with Bullnose Cap, 4000 lb. with Assist	
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback				36" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Round Top Seamless Aluminum					
<b>Roof Cap</b>	TPO					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 10K

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 12	8.5 x 14
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**SHOCKWAVE CARGO**  
**SHOCKWAVE ROUND TOP ROUND FRONT 10K**

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Model #</b>	FI10216THRF-100	FI10218THRF-100	FI10220THRF-100	FI10222THRF-100	FI10224THRF-100	FI10226THRF-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Round					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Round Top Seamless Aluminum					
<b>Roof Cap</b>	TPO					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 3K

	6 x 10	6 x 12	6 x 14	7 x 12
<b>Model #</b>	FI7210THRF-030	FI7212THRF-030	FI7214THRF-030	FI8412THRF-035
<b>CAPACITIES</b>				
<b>GVWR (lbs)</b>	2990			3500
<b>GAWR (lbs/axle)</b>	3500			
<b>CHASSIS</b>				
<b>Frame</b>	4" x 2" Steel Tube			
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension		6" Extension, 6" x 2" Steel Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center			
<b>Coupler</b>	2" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard			
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue			
<b>Tongue Jack</b>	2K Set-Back			
<b>Wall Studs</b>	Steel Tube, 16" On-Center			
<b>Roof Bows</b>	Steel Tube, 16" On-Center			
<b>Front Profile</b>	Round			
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist		12" Extension with Bullnose Cap, 2500 lb. with Assist	
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback			
<b>Fenders</b>	Aluminum Treadplate			
<b>Axle</b>	3500 lb. Drop Spring Idler		3500 lb. Drop Spring Brake	
<b>Hubs</b>	Easy Lube			
<b>Breakaway</b>	Battery, Switch, and Lanyard			
<b>Tires</b>	ST205/75R15C 6-PR			
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps			
<b>Exterior Finish</b>	.030" Aluminum			
<b>Undercoating</b>	Automotive			
<b>Exterior Fastening</b>	VHB Bonded (Screwless)			
<b>Exterior Trim</b>	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop			
<b>Stone Guard</b>	24" ATP			
<b>Roof</b>	Round Top Seamless Aluminum			
<b>Roof Cap</b>	TPO			
<b>Interior Walls</b>	Engineered Wood			
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions			
<b>Ceiling</b>	White ThermoPly®			
<b>Flooring</b>	3/4" Engineered Wood			
<b>Interior Lights</b>	(2) LED			
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V			
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings			
<b>Connector Plug</b>	Flat 4-pin, Holder on Tongue, Holder on Tongue		Holder on Tongue, Holder on Tongue, Round 7-pin Blade	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 3K

	6 x 10	6 x 12	6 x 14	7 x 12
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant			(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 7K

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
<b>Model #</b>	FI7212THRF-070	FI8412THRF-070	FI8414THRF-070	FI8416THRF-070	FI8418THRF-070	FI8420THRF-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	4" x 2" Steel Tube			6" x 2" Steel Tube		
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension		6" Extension, 6" x 2" Steel Tube			
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	Round					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist		12" Extension with Bullnose Cap, 2500 lb. with Assist			
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST205/75R15C 6-PR					
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" ATP					
<b>Roof</b>	Round Top Seamless Aluminum					
<b>Roof Cap</b>	TPO					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CARGO  
SHOCKWAVE ROUND TOP ROUND FRONT 7K

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 7K

	7 x 20	8.5 x 12	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22
<b>Model #</b>	FI8420THSV-070	FI10212THSV-070	FI10216THRF-070	FI10218THRF-070	FI10220THRF-070	FI10222THRF-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Tube	6" Extension, 6" x 2" Steel Triple Tube				
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop	30" Sloped V-Nose with 12" Drop	Round			
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist	12" Extension with Bullnose Cap, 4000 lb. with Assist				
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback	36" Wide Flush Lock, Cast Aluminum Holdback				
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST205/75R15C 6-PR					
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop				
<b>Stone Guard</b>	24" Sloped ATP	24" ATP				
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum	Round Top Seamless Aluminum				
<b>Roof Cap</b>	TPO					
<b>Interior Walls</b>	Engineered Wood					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.







# SHOCKWAVE CARGO SHOCKWAVE ROUND TOP ROUND FRONT 7K

	7 x 20	8.5 x 12	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**SHOCKWAVE CARGO**  
**SHOCKWAVE ROUND TOP ROUND FRONT 7K**

**8.5 x 24**

<b>Model #</b>	FI10224THRF-070
<b>CAPACITIES</b>	
<b>GVWR (lbs)</b>	7000
<b>GAWR (lbs/axle)</b>	3500
<b>CHASSIS</b>	
<b>Frame</b>	6" x 2" Steel Tube
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center
<b>Integrated Step(s)</b>	Interior Recessed
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue
<b>Tongue Jack</b>	2K Set-Back
<b>Wall Studs</b>	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
<b>Front Profile</b>	Round
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback
<b>Fenders</b>	Aluminum Treadplate
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube
<b>Breakaway</b>	Battery, Switch, and Lanyard
<b>Tires</b>	ST205/75R15C 6-PR
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps
<b>Exterior Finish</b>	.030" Aluminum
<b>Undercoating</b>	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
<b>Exterior Trim</b>	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, Brite Aluminum Radius Front Corners, Brite Aluminum Rear Hoop
<b>Stone Guard</b>	24" ATP
<b>Roof</b>	Round Top Seamless Aluminum
<b>Roof Cap</b>	TPO
<b>Interior Walls</b>	Engineered Wood
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions
<b>Ceiling</b>	White ThermoPly®
<b>Flooring</b>	3/4" Engineered Wood
<b>Interior Lights</b>	(2) LED
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K**

	7 x 14	7 x 16	7 x 18	7 x 20	7.5 x 14	7.5 x 16
<b>Model #</b>	FI8414THSV-100	FI8416THSV-100	FI8418THSV-100	FI8420THSV-100	FI9014THSV-100	FI9016THSV-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist					
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K**

	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14	8.5 x 16	8.5 x 18
<b>Model #</b>	FI9018THSV-100	FI9020THSV-100	FI10212THSV-100	FI10214THSV-100	FI10216THSV-100	FI10218THSV-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Tube			6" Extension, 6" x 2" Steel Triple Tube		
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>				Interior Recessed		
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop			30" Sloped V-Nose with 12" Drop		
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist			12" Extension with Bullnose Cap, 4000 lb. with Assist		
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback			36" Wide Flush Lock, Cast Aluminum Holdback		
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CARGO  
SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K

	7.5 x 18	7.5 x 20	8.5 x 12	8.5 x 14	8.5 x 16	8.5 x 18
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Model #</b>	FI10220THSV-100	FI10222THSV-100	FI10224THSV-100	FI10226THSV-100	FI10228THSV-100	FI10230THSV-100
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	9900					
<b>GAWR (lbs/axle)</b>	5000					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube				8" x 2" Steel Tube	
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube				6" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back				5K Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	30" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST225/75R15D 8-PR					
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 10K**

	8.5 x 32	8.5 x 34
<b>Model #</b>	F110232THSV-100	F110234THSV-100
<b>CAPACITIES</b>		
<b>GVWR (lbs)</b>	9900	
<b>GAWR (lbs/axle)</b>	5000	
<b>CHASSIS</b>		
<b>Frame</b>	8" x 2" Steel Tube	
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center	
<b>Integrated Step(s)</b>	Interior Recessed	
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard	
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue	
<b>Tongue Jack</b>	5K Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center	
<b>Roof Bows</b>	Steel Tube, 16" On-Center	
<b>Front Profile</b>	30" Sloped V-Nose with 12" Drop	
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist	
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate	
<b>Axle</b>	(2) 5200 lb. Drop Spring Brake	
<b>Hubs</b>	Easy Lube	
<b>Breakaway</b>	Battery, Switch, and Lanyard	
<b>Tires</b>	ST225/75R15D 8-PR	
<b>Wheels</b>	15", 6-Hole Aluminum, Stainless Center Caps	
<b>Exterior Finish</b>	.030" Aluminum	
<b>Undercoating</b>	Automotive	
<b>Exterior Fastening</b>	VHB Bonded (Screwless)	
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop	
<b>Stone Guard</b>	24" Sloped ATP	
<b>Rear Spoiler</b>	9" Brite Aluminum Flare	
<b>Roof</b>	Flat Top Seamless Aluminum	
<b>Interior Walls</b>	Engineered Wood	
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions	
<b>Ceiling</b>	White ThermoPly®	
<b>Flooring</b>	3/4" Engineered Wood	
<b>Interior Lights</b>	(2) LED	
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings	
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K**

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 16	8.5 x 18
<b>Model #</b>	F18414THSV-140	F18416THSV-140	F18418THSV-140	F18420THSV-140	F110216THSV-140	F110218THSV-140
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	14000					
<b>GAWR (lbs/axle)</b>	7000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	7K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop				30" Sloped V-Nose with 12" Drop	
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist				12" Extension with Bullnose Cap, 4000 lb. with Assist	
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback				36" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 8000 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST235/80R16E 10-PR					
<b>Wheels</b>	16", 8-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.







SHOCKWAVE CARGO  
SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K

	7 x 14	7 x 16	7 x 18	7 x 20	8.5 x 16	8.5 x 18
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 14K**

	8.5 x 20	8.5 x 24
<b>Model #</b>	F110220THSV-140	F110224THSV-140
<b>CAPACITIES</b>		
<b>GVWR (lbs)</b>	14000	
<b>GAWR (lbs/axle)</b>	7000	
<b>CHASSIS</b>		
<b>Frame</b>	8" x 2" Steel Tube	
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center	
<b>Integrated Step(s)</b>	Interior Recessed	
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard	
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue	
<b>Tongue Jack</b>	7K Drop Leg, Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center	
<b>Roof Bows</b>	Steel Tube, 16" On-Center	
<b>Front Profile</b>	30" Sloped V-Nose with 12" Drop	
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist	
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate	
<b>Axle</b>	(2) 8000 lb. Drop Spring Brake	
<b>Hubs</b>	Easy Lube	
<b>Breakaway</b>	Battery, Switch, and Lanyard	
<b>Tires</b>	ST235/80R16E 10-PR	
<b>Wheels</b>	16", 8-Hole Aluminum, Stainless Center Caps	
<b>Exterior Finish</b>	.030" Aluminum	
<b>Undercoating</b>	Automotive	
<b>Exterior Fastening</b>	VHB Bonded (Screwless)	
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop	
<b>Stone Guard</b>	24" Sloped ATP	
<b>Rear Spoiler</b>	9" Brite Aluminum Flare	
<b>Roof</b>	Flat Top Seamless Aluminum	
<b>Interior Walls</b>	Engineered Wood	
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions	
<b>Ceiling</b>	White ThermoPly®	
<b>Flooring</b>	3/4" Engineered Wood	
<b>Interior Lights</b>	(2) LED	
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings	
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 16K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 30
<b>Model #</b>	FI10220THSV-160	FI10222THSV-160	FI10224THSV-160	FI10226THSV-160	FI10228THSV-160	FI10230THSV-160
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	16000					
<b>GAWR (lbs/axle)</b>	7000					
<b>CHASSIS</b>						
<b>Frame</b>	8" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 8" x 2" Steel Triple Tube					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>	Interior Recessed					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	12K Drop Leg, Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	30" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist					
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 8000 lb. Drop Spring Brake					
<b>Hubs</b>	Oil Bath					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	215/75R17.5J 18-PR					
<b>Wheels</b>	17.5", 8-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





# SHOCKWAVE CARGO SHOCKWAVE FLAT TOP SLOPED V-NOSE 3K

	5 x 8	5 x 8	5 x 10	5 x 10	6 x 10	6 x 10
<b>Model #</b>	FI6008THSV-035	FI6008THSV-030	FI6010THSV-035	FI6010THSV-030	FI7210THSV-050	FI7210THSV-035
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	3500	2990	3500	2990	5000	3500
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	4" x 2" Steel Tube					
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist					
<b>Side Door</b>					32" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	5200 lb. Drop Spring Brake	3500 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard		Battery, Switch, and Lanyard		Battery, Switch, and Lanyard	
<b>Tires</b>	ST205/75R15C 6-PR				ST225/75R15D 8-PR	ST205/75R15C 6-PR
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps				15", 6-Hole Aluminum, Stainless Center Caps	15", 5-Hole Aluminum, Stainless Center Caps
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 3K**

	5 x 8	5 x 8	5 x 10	5 x 10	6 x 10	6 x 10
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	Flat 4-pin, Holder on Tongue, Holder on Tongue	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	Flat 4-pin, Holder on Tongue, Holder on Tongue	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	(1) Rear LED Loading, Full LED, DOT Compliant	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	(1) Rear LED Loading, Full LED, DOT Compliant	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 3K**

	6 x 10	6 x 12	6 x 12	6 x 12	6 x 14	6 x 14
<b>Model #</b>	FI7210THSV-030	FI7212THSV-035	FI7212THSV-030	FI7212THSV-050	FI7214THSV-035	FI7214THSV-050
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	2990	3500	2990	5000	3500	5000
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	4" x 2" Steel Tube					
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension					
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist					
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake	3500 lb. Drop Spring Idler	5200 lb. Drop Spring Brake	3500 lb. Drop Spring Brake	5200 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard		Battery, Switch, and Lanyard			
<b>Tires</b>	ST205/75R15C 6-PR			ST225/75R15D 8-PR	ST205/75R15C 6-PR	ST225/75R15D 8-PR
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps			15", 6-Hole Aluminum, Stainless Center Caps	15", 5-Hole Aluminum, Stainless Center Caps	15", 6-Hole Aluminum, Stainless Center Caps
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 3K**

	6 x 10	6 x 12	6 x 12	6 x 12	6 x 14	6 x 14
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Flat 4-pin, Holder on Tongue, Holder on Tongue	Holder on Tongue, Holder on Tongue, Round 7-pin Blade	Flat 4-pin, Holder on Tongue, Holder on Tongue	Holder on Tongue, Holder on Tongue, Round 7-pin Blade		
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights	(1) Rear LED Loading, Full LED, DOT Compliant	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights		

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 3K**

	6 x 14	7 x 12
<b>Model #</b>	FI7214THSV-030	FI8412THSV-035
<b>CAPACITIES</b>		
<b>GVWR (lbs)</b>	2990	3500
<b>GAWR (lbs/axle)</b>	3500	
<b>CHASSIS</b>		
<b>Frame</b>	4" x 2" Steel Tube	
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension	6" Extension, 6" x 2" Steel Tube
<b>Crossmembers</b>	Formed Steel, 16" On-Center	
<b>Coupler</b>	2" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard	
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue	
<b>Tongue Jack</b>	2K Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center	
<b>Roof Bows</b>	Steel Tube, 16" On-Center	
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop	
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist	12" Extension with Bullnose Cap, 2500 lb. with Assist
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback	
<b>Fenders</b>	Aluminum Treadplate	
<b>Axle</b>	3500 lb. Drop Spring Idler	3500 lb. Drop Spring Brake
<b>Hubs</b>	Easy Lube	
<b>Breakaway</b>	Battery, Switch, and Lanyard	
<b>Tires</b>	ST205/75R15C 6-PR	
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps	
<b>Exterior Finish</b>	.030" Aluminum	
<b>Undercoating</b>	Automotive	
<b>Exterior Fastening</b>	VHB Bonded (Screwless)	
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop	
<b>Stone Guard</b>	24" Sloped ATP	
<b>Rear Spoiler</b>	9" Brite Aluminum Flare	
<b>Roof</b>	Flat Top Seamless Aluminum	
<b>Interior Walls</b>	Engineered Wood	
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions	
<b>Ceiling</b>	White ThermoPly®	
<b>Flooring</b>	3/4" Engineered Wood	
<b>Interior Lights</b>	(2) LED	
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V	
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings	
<b>Connector Plug</b>	Flat 4-pin, Holder on Tongue, Holder on Tongue	Holder on Tongue, Holder on Tongue, Round 7-pin Blade
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.







**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K**

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7.5 x 14
<b>Model #</b>	FI7212THSV-070	FI8412THSV-070	FI8414THSV-070	FI8416THSV-070	FI8418THSV-070	FI9014THSV-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	4" x 2" Steel Tube			6" x 2" Steel Tube		
<b>Tongue</b>	4" x 2" Steel Tube, 6" Extension		6" Extension, 6" x 2" Steel Tube			
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop					
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 1500 lb. with Assist		12" Extension with Bullnose Cap, 2500 lb. with Assist			
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback					
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST205/75R15C 6-PR					
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CARGO  
SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

6 x 12

7 x 12

7 x 14

7 x 16

7 x 18

7.5 x 14

**Exterior Lights**

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



**SHOCKWAVE CARGO**  
**SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K**

	7.5 x 16	7.5 x 18	7.5 x 20	8.5 x 14	8.5 x 16	8.5 x 18
<b>Model #</b>	FI9016THSV-070	FI9018THSV-070	FI9020THSV-070	FI10214THSV-070	FI10216THSV-070	FI10218THSV-070
<b>CAPACITIES</b>						
<b>GVWR (lbs)</b>	7000					
<b>GAWR (lbs/axle)</b>	3500					
<b>CHASSIS</b>						
<b>Frame</b>	6" x 2" Steel Tube					
<b>Tongue</b>	6" Extension, 6" x 2" Steel Tube			6" Extension, 6" x 2" Steel Triple Tube		
<b>Crossmembers</b>	Formed Steel, 16" On-Center					
<b>Integrated Step(s)</b>				Interior Recessed		
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard					
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue					
<b>Tongue Jack</b>	2K Set-Back					
<b>Wall Studs</b>	Steel Tube, 16" On-Center					
<b>Roof Bows</b>	Steel Tube, 16" On-Center					
<b>Front Profile</b>	24" Sloped V-Nose with 12" Drop, 24" Sloped V-Nose with 12" Drop			30" Sloped V-Nose with 12" Drop		
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 2500 lb. with Assist			12" Extension with Bullnose Cap, 4000 lb. with Assist		
<b>Side Door</b>	32" Wide Flush Lock, Cast Aluminum Holdback			36" Wide Flush Lock, Cast Aluminum Holdback		
<b>Fenders</b>	Aluminum Treadplate					
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake					
<b>Hubs</b>	Easy Lube					
<b>Breakaway</b>	Battery, Switch, and Lanyard					
<b>Tires</b>	ST205/75R15C 6-PR					
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps					
<b>Exterior Finish</b>	.030" Aluminum					
<b>Undercoating</b>	Automotive					
<b>Exterior Fastening</b>	VHB Bonded (Screwless)					
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop					
<b>Stone Guard</b>	24" Sloped ATP					
<b>Rear Spoiler</b>	9" Brite Aluminum Flare					
<b>Roof</b>	Flat Top Seamless Aluminum					
<b>Interior Walls</b>	Engineered Wood					
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions					
<b>Ceiling</b>	White ThermoPly®					
<b>Flooring</b>	3/4" Engineered Wood					
<b>Interior Lights</b>	(2) LED					
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V					
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings					
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.





SHOCKWAVE CARGO  
SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

7.5 x 16

7.5 x 18

7.5 x 20

8.5 x 14

8.5 x 16

8.5 x 18

**Exterior Lights**

(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights



Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.



# SHOCKWAVE CARGO SHOCKWAVE FLAT TOP SLOPED V-NOSE 7K

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28
<b>Model #</b>	F110220THSV-070	F110222THSV-070	F110224THSV-070	F110226THSV-070	F110228THSV-070
<b>CAPACITIES</b>					
<b>GVWR (lbs)</b>	7000				
<b>GAWR (lbs/axle)</b>	3500				
<b>CHASSIS</b>					
<b>Frame</b>	6" x 2" Steel Tube			8" x 2" Steel Tube	
<b>Tongue</b>	6" Extension, 6" x 2" Steel Triple Tube			6" Extension, 8" x 2" Steel Triple Tube	
<b>Crossmembers</b>	Formed Steel, 16" On-Center				
<b>Integrated Step(s)</b>	Interior Recessed				
<b>Coupler</b>	2-5/16" Adjustable, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard				
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue				
<b>Tongue Jack</b>	2K Set-Back			5K Set-Back	
<b>Wall Studs</b>	Steel Tube, 16" On-Center				
<b>Roof Bows</b>	Steel Tube, 16" On-Center				
<b>Front Profile</b>	30" Sloped V-Nose with 12" Drop				
<b>Ramp(s)</b>	12" Extension with Bullnose Cap, 4000 lb. with Assist				
<b>Side Door</b>	36" Wide Flush Lock, Cast Aluminum Holdback				
<b>Fenders</b>	Aluminum Treadplate				
<b>Axle</b>	(2) 3500 lb. Drop Spring Brake				
<b>Hubs</b>	Easy Lube				
<b>Breakaway</b>	Battery, Switch, and Lanyard				
<b>Tires</b>	ST205/75R15C 6-PR				
<b>Wheels</b>	15", 5-Hole Aluminum, Stainless Center Caps				
<b>Exterior Finish</b>	.030" Aluminum				
<b>Undercoating</b>	Automotive				
<b>Exterior Fastening</b>	VHB Bonded (Screwless)				
<b>Exterior Trim</b>	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Brite Aluminum Rear Hoop				
<b>Stone Guard</b>	24" Sloped ATP				
<b>Rear Spoiler</b>	9" Brite Aluminum Flare				
<b>Roof</b>	Flat Top Seamless Aluminum				
<b>Interior Walls</b>	Engineered Wood				
<b>Interior Trim</b>	Extruded Aluminum Wall Transitions				
<b>Ceiling</b>	White ThermoPly®				
<b>Flooring</b>	3/4" Engineered Wood				
<b>Interior Lights</b>	(2) LED				
<b>Switches</b>	(1) Top Fuel Dome Light, 12V, (1) Top Fuel Load Light, 12V				
<b>Cargo Control</b>	(4) 5000 lb. Recessed D-Rings				
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade				
<b>Exterior Lights</b>	(1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights				

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

