



**SUB-ZERO ALUMINUM MOTORSPORT
SUB-ZERO FLAT TOP SLOPED V-NOSE 7K**

	7 x 19	7 x 23	7 x 27	7 x 29
Model #	FI8419TPSVA-070	FI8423TPSVA-070	FI8427TPSVA-070	FI8429TPSVA-070
CAPACITIES				
GVWR (lbs)	7000			
GAWR (lbs/axle)	3500			
CHASSIS				
Frame	5" x 2" Double Hollow Aluminum Tube			
Tongue	5" x 3" Double Hollow Aluminum Straight Tube			
Crossmembers	Aluminum Tube, 16" On-Center			
Coupler	2-5/16" Straight Demco			
Safety Chains	DOT Compliant			
Tongue Jack	2K Frame Mounted			
Wall Studs	Aluminum Tube, 16" On-Center			
Roof Bows	Aluminum Tube, 16" On-Center			
Front Profile	60" Sloped V-Nose with 6" Drop			
Ramp(s)	12" Extension with Hingeless Brackets (Both Ramps), 2500 lb. with Assist, 61" Front Wedge with Assist			
Side Door	32" Wide Flush Lock, Wire Holdback	36" Wide Flush Lock, Wire Holdback		
Vents	Sidewall Airflow			
Fenders	Aluminum Treadplate			
Axle	(2) 3500 lb. Drop Spring Brake			
Hubs	Easy Lube			
Breakaway	Battery, Switch, and Lanyard			
Tires	ST205/75R15C 6-PR			
Wheels	15", 5-Hole Steel, Center Caps and Beauty Rings1			
Exterior Finish	.030" Aluminum			
Exterior Fastening	VHB Bonded (Screwless)			
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop			
Stone Guard	16" Sloped ATP, 16" Sloped ATP			
Rear Spoiler	9" Flare			
Roof	Flat Top Seamless Aluminum			
Interior Trim	3/4" Engineered Wood Kickplate, 12" Tall, Engineered Wood Wall Transitions			
Ceiling	Lauan Strip			
Flooring	3/4" Engineered Wood			
Switches	(1) Dome Light, 12V, (2) Load Light, 12V			
Cargo Control	(9) 2.5K Recessed D-Rings			
Connector Plug	Round 7-pin Blade			
Exterior Lights	(1) Front LED Loading, (1) Rear LED Loading, Full LED, DOT Compliant, Integrated Backup/Taillights			

Specifications and Pricing subject to change without notice, please reference confirmation sheet for final pricing.

