

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26				
Model #	FI10216CQRFCH-	FI10218CQRFCH-	FI10220CQRFCH-	FI10222CQRFCH-	FI10224CQRFCH-	FI10226CQRFCH-				
Model #	100	100	100	100	100	100				
CAPACITIES										
GVWR (lbs)			99	000						
GAWR (lbs/axle)	5000									
CHASSIS										
Frame		6" x 2" Steel Tube								
Tongue			6" x 2" Stee	l Triple Tube						
Crossmembers			Formed Steel,	16" On-Center						
Integrated Step(s)			Interior I	Recessed						
Coupler	2-	5/16" A-Frame, Conr	nected Latch Pin with	Lanyard, Connected	Latch Pin with Lanya	ırd				
Safety Chains		DOT C	ompliant, Holders on	Tongue, Holders on	Tongue					
Tongue Jack			2K Couple	er Mounted						
Wall Studs			Steel Tube, 1	6" On-Center						
Roof Bows			•	6" On-Center						
Front Profile			30" Sloped V-No	se with 12" Drop						
Beavertail	32"			48"						
Ramp(s)			•	000 lb. with Assist						
Side Door				ck, Wire Holdback						
Vents				l Airflow						
Fenders				Treadplate						
Axle			• • • • • • • • • • • • • • • • • • • •	op Spring Brake						
Hubs			•	Lube						
Breakaway				h, and Lanyard						
Tires			,	R15D 8-PR						
Wheels		15", 6-Hole	e Steel, Stainless Cer	· ·	Center Caps					
Exterior Finish				luminum 						
Undercoating				notive						
Exterior Fastening Exterior Trim	000 Al	inum Doof Covo 2.7		l (Screwless)	ara Calar Matahina	Door Hoon				
Stone Guard	.060 Aluli	illiulli Rooi Cove, 2.7	Bottom Extrusion, A	ATP	iers, color matching	кеат поор				
Roof				nless Aluminum						
Roof Cap			·	PO						
Interior Walls				red Wood						
Interior Trim				Transitions						
Ceiling				n Strip						
Flooring				eered Wood						
Interior Lights				LED						
Switches			, ,	Light, 12V						







	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	
Cargo Control	(4) 5000 lb. Recessed D-Rings						
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade						
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights						





	8.5 x 28
Model #	FI10228CQRFCH-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	2K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Steel, Stainless Center Caps, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
<b>Exterior Fastening</b>	VHB Bonded (Screwless)
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, ATP Radius Front Corners, Color Matching Rear Hoop
Stone Guard	24" ATP
Roof	Round Top Seamless Aluminum
Roof Cap	TPO
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade







	8.5 x 28
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights





	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26				
Model #	FI10216CQRFCH-	FI10218CQRFCH-	FI10220CQRFCH-	FI10222CQRFCH-	FI10224CQRFCH-	FI10226CQRFCH-				
wodei #	070	070	070	070	070	070				
CAPACITIES										
GVWR (lbs)			70	00						
GAWR (lbs/axle)	3500									
CHASSIS										
Frame		6" x 2" Steel Tube								
Tongue			6" x 2" Stee	l Triple Tube						
Crossmembers			Formed Steel,	16" On-Center						
Integrated Step(s)			Interior I	Recessed						
Coupler	2-	-5/16" A-Frame, Conr	nected Latch Pin with	Lanyard, Connected	Latch Pin with Lanya	ırd				
Safety Chains		DOT C	ompliant, Holders on	Tongue, Holders on	Tongue					
Tongue Jack			2K Couple	r Mounted						
Wall Studs			Steel Tube, 1	6" On-Center						
Roof Bows			Steel Tube, 1	6" On-Center						
Front Profile			30" Sloped V-No	se with 12" Drop						
Beavertail	32"			48"						
Ramp(s)			•	00 lb. with Assist						
Side Door				ck, Wire Holdback						
Vents				l Airflow						
Fenders				Treadplate						
Axle			• • • • • • • • • • • • • • • • • • • •	op Spring Brake						
Hubs			•	Lube						
Breakaway			•	h, and Lanyard						
Tires				R15C 6-PR						
Wheels		15", 5-Hole	e Steel, Stainless Cer		Center Caps					
Exterior Finish				uminum						
Undercoating				notive						
Exterior Fastening Exterior Trim	000 Alum	ninum Poof Covo. 2.7	V חם Bolluet Bottom Extrusion, A "	l (Screwless) TD Badius Front Core	ore Color Matching	Door Hoon				
Stone Guard	.000 Aluli	illiulli Rooi Gove, 2.7		ATP	iers, color Matching	кеат поор				
Roof				nless Aluminum						
Roof Cap			·	20						
Interior Walls				red Wood						
Interior Trim				Transitions						
Ceiling				n Strip						
Flooring				eered Wood						
Interior Lights				LED						
Switches			, ,	Light, 12V						







	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26		
Cargo Control	(4) 5000 lb. Recessed D-Rings							
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade							
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights							





	8.5 x 28
Model #	FI10228CQRFCH-070
	TTTOZZOCQNI CIT-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
Safety Chains	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center
Roof Bows	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Steel, Stainless Center Caps, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	.080 Aluminum Roof Cove, 2.7" Bottom Extrusion, ATP Radius Front Corners, Color Matching Rear Hoop
Stone Guard	24" ATP
Roof	Round Top Seamless Aluminum
Roof Cap	TPO
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade







	8.5 x 28
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights





## **TREMOR FLAT TOP SLOPED V-NOSE 10K**

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26			
Madel #	FI10216CQSVCH-	FI10218CQSVCH-	FI10220CQSVCH-	FI10222CQSVCH-	FI10224CQSVCH-	FI10226CQSVCH-			
Model #	100	100	100	100	100	100			
CAPACITIES									
GVWR (lbs)			99	00					
GAWR (lbs/axle)	5000								
CHASSIS									
Frame			6" x 2" S	teel Tube					
Tongue			6" x 2" Stee	Triple Tube					
Crossmembers			Formed Steel,	16" On-Center					
Integrated Step(s)			Interior F	Recessed					
Coupler	2-	-5/16" A-Frame, Conr	nected Latch Pin with	Lanyard, Connected	Latch Pin with Lanya	ırd			
Safety Chains		DOT C	ompliant, Holders on	Tongue, Holders on	Tongue				
Tongue Jack			2K Couple	r Mounted					
Wall Studs			Steel Tube, 1	6" On-Center					
<b>Roof Bows</b>			Steel Tube, 1	6" On-Center					
Front Profile		30" Sloped V-Nose with 12" Drop							
Beavertail	32"			48"					
Ramp(s)			16" Extension, 40	00 lb. with Assist					
Side Door			36" Wide Flush Lo	ck, Wire Holdback					
Vents			Sidewal	l Airflow					
Fenders			Aluminum	Treadplate					
Axle			• •	op Spring Brake					
Hubs			•	Lube					
Breakaway			•	h, and Lanyard					
Tires				R15D 8-PR					
Wheels		15", 6-Hole	e Steel, Stainless Cen	· ·	Center Caps				
Exterior Finish				uminum					
Undercoating				notive					
Exterior Fastening				(Screwless)					
Exterior Trim		2.7" Bottom Extrusion	n, 2.7" Top Extrusion,	•	r Matching Rear Hoo	p			
Stone Guard			•	ped ATP					
Roof			•	less Aluminum					
Interior Walls				ed Wood					
Interior Trim			•	Transitions					
Ceiling				n Strip					
Flooring				eered Wood					
Interior Lights			* *	LED					
Switches			` '	Light, 12V					
Cargo Control			(4) 5000 lb. Re	cessed D-Rings					







## **TREMOR FLAT TOP SLOPED V-NOSE 10K**

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26		
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade							
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights							





## **TREMOR FLAT TOP SLOPED V-NOSE 10K**

	8.5 x 28
Model #	FI10228CQSVCH-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5000
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	2K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 5200 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST225/75R15D 8-PR
Wheels	15", 6-Hole Steel, Stainless Center Caps, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop
Stone Guard	24" Sloped ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights







## **TREMOR FLAT TOP SLOPED V-NOSE 14K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 30					
Model #	FI10220CQSVCH-140	FI10222CQSVCH-140	FI10224CQSVCH-140	FI10226CQSVCH-140	FI10230CQSVCH-140					
CAPACITIES										
GVWR (lbs)			14000							
GAWR (lbs/axle)			7000							
CHASSIS										
Frame			8" x 2" Steel Tube							
Tongue			8" x 2" Steel Triple Tube							
Crossmembers		F	ormed Steel, 16" On-Cent	er						
Integrated Step(s)			Interior Recessed							
Coupler	2-5/16'	' Adjustable, Connected I	Latch Pin with Lanyard, Co	onnected Latch Pin with I	Lanyard					
Safety Chains		DOT Complian	t, Holders on Tongue, Hol	ders on Tongue						
Tongue Jack			7K Drop Leg, Set-Back							
Wall Studs			Steel Tube, 16" On-Cente	r						
Roof Bows			Steel Tube, 16" On-Cente	r						
Front Profile		30"	Sloped V-Nose with 12" [	Orop						
Beavertail			48"							
Ramp(s)		16" I	Extension, 4000 lb. with A	ssist						
Side Door		36" V	Vide Flush Lock, Wire Hold	dback						
Vents			Sidewall Airflow							
Fenders			Aluminum Treadplate							
Axle		(2	) 7000 lb. Drop Spring Bra	ike						
Hubs			Easy Lube							
Breakaway		В	attery, Switch, and Lanya	rd						
Tires			ST235/80R16E 10-PR							
Wheels		16", 8-Hole Steel, S	Stainless Center Caps, Sta	ninless Center Caps						
Exterior Finish			.030" Aluminum							
Undercoating			Automotive							
<b>Exterior Fastening</b>			VHB Bonded (Screwless)							
Exterior Trim	2.7"	Bottom Extrusion, 2.7" To	op Extrusion, ATP Nose C	ap, Color Matching Rear	Ноор					
Stone Guard			24" Sloped ATP							
Roof		FI	at Top Seamless Aluminu	i <b>m</b>						
Interior Walls			Engineered Wood							
Interior Trim			Vinyl Wall Transitions							
Ceiling			Lauan Strip							
Flooring			3/4" Engineered Wood							
Interior Lights			(2) LED							
Switches			(1) Dome Light, 12V							
Cargo Control		•	) 5000 lb. Recessed D-Rin	•						
Connector Plug		Holder on Tong	ue, Holder on Tongue, Ro	und 7-pin Blade						





### **TREMOR CAR HAULER**

## **TREMOR FLAT TOP SLOPED V-NOSE 14K**

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 30
<b>Exterior Lights</b>	Full LED, DOT Compliant, Integrated Backup/Taillights				





## TREMOR FLAT TOP SLOPED V-NOSE 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
Model #	FI10216CQSVCH-	FI10218CQSVCH-	FI10220CQSVCH-	FI10222CQSVCH-	FI10224CQSVCH-	FI10226CQSVCH-
Model #	070	070	070	070	070	070
CAPACITIES						
GVWR (lbs)			70	00		
GAWR (lbs/axle)			35	00		
CHASSIS						
Frame			6" x 2" Steel Tube			8" x 2" Steel Tube
Tongue			6" x 2" Stee	l Triple Tube		
Crossmembers			Formed Steel,	16" On-Center		
Integrated Step(s)			Interior F	Recessed		
Coupler	2-	5/16" A-Frame, Conr	nected Latch Pin with	Lanyard, Connected	Latch Pin with Lanya	ırd
Safety Chains		DOT C	ompliant, Holders on	Tongue, Holders on	Tongue	
Tongue Jack		2K Coupler Mounted				
Wall Studs	Steel Tube, 16" On-Center					
<b>Roof Bows</b>			Steel Tube, 1	6" On-Center		
Front Profile	30" Sloped V-Nose with 12" Drop					
Beavertail	32"			48"		
Ramp(s)	16" Extension, 4000 lb. with Assist					
Side Door	36" Wide Flush Lock, Wire Holdback					
Vents	Sidewall Airflow					
Fenders	Aluminum Treadplate					
Axle	(2) 3500 lb. Drop Spring Brake					
Hubs	Easy Lube					
Breakaway	Battery, Switch, and Lanyard					
Tires	ST205/75R15C 6-PR					
Wheels	15", 5-Hole Steel, Stainless Center Caps, Stainless Center Caps					
Exterior Finish	.030" Aluminum					
Undercoating	Automotive					
Exterior Fastening	VHB Bonded (Screwless)					
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop					
Stone Guard	24" Sloped ATP					
Roof Interior Walls	Flat Top Seamless Aluminum					
Interior Walls	Engineered Wood					
Ceiling	Vinyl Wall Transitions					
Flooring	Lauan Strip					
Interior Lights	3/4" Engineered Wood					
Switches	(2) LED (1) Dome Light, 12V					
Cargo Control		(1) Dome Light, 12V (4) 5000 lb. Recessed D-Rings				
Caryo Cuntru			(4) 5000 lb. Re	cesseu D-Killys		







## TREMOR FLAT TOP SLOPED V-NOSE 7K

	8.5 x 16	8.5 x 18	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26
<b>Connector Plug</b>	Holder on Tongue, Holder on Tongue, Round 7-pin Blade					
<b>Exterior Lights</b>		Full LI	ED, DOT Compliant, Ir	ntegrated Backup/Ta	illights	





## TREMOR FLAT TOP SLOPED V-NOSE 7K

	8.5 x 28
Model #	FI10228CQSVCH-070
CAPACITIES	
GVWR (lbs)	7000
GAWR (lbs/axle)	3500
CHASSIS	
Frame	8" x 2" Steel Tube
Tongue	8" x 2" Steel Triple Tube
Crossmembers	Formed Steel, 16" On-Center
Integrated Step(s)	Interior Recessed
Coupler	2-5/16" A-Frame, Connected Latch Pin with Lanyard, Connected Latch Pin with Lanyard
<b>Safety Chains</b>	DOT Compliant, Holders on Tongue, Holders on Tongue
Tongue Jack	5K Coupler Mounted
Wall Studs	Steel Tube, 16" On-Center
<b>Roof Bows</b>	Steel Tube, 16" On-Center
Front Profile	30" Sloped V-Nose with 12" Drop
Beavertail	48"
Ramp(s)	16" Extension, 4000 lb. with Assist
Side Door	36" Wide Flush Lock, Wire Holdback
Vents	Sidewall Airflow
Fenders	Aluminum Treadplate
Axle	(2) 3500 lb. Drop Spring Brake
Hubs	Easy Lube
Breakaway	Battery, Switch, and Lanyard
Tires	ST205/75R15C 6-PR
Wheels	15", 5-Hole Steel, Stainless Center Caps, Stainless Center Caps
Exterior Finish	.030" Aluminum
Undercoating	Automotive
Exterior Fastening	VHB Bonded (Screwless)
Exterior Trim	2.7" Bottom Extrusion, 2.7" Top Extrusion, ATP Nose Cap, Color Matching Rear Hoop
Stone Guard	24" Sloped ATP
Roof	Flat Top Seamless Aluminum
Interior Walls	Engineered Wood
Interior Trim	Vinyl Wall Transitions
Ceiling	Lauan Strip
Flooring	3/4" Engineered Wood
Interior Lights	(2) LED
Switches	(1) Dome Light, 12V
Cargo Control	(4) 5000 lb. Recessed D-Rings
Connector Plug	Holder on Tongue, Holder on Tongue, Round 7-pin Blade
Exterior Lights	Full LED, DOT Compliant, Integrated Backup/Taillights

